

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


*Omit weld at seal opening.

**When joint is fixed, dimension
is set at 1½".




SECTION THRU STRIP SEAL JOINT FOR OVERLAY OVER DECK BEAMS






LOCKING EDGE RAIL

LOCKING EDGE RAIL SPLICE





SECTION A-A

POINT BLOCK DETAILS

Notes: The strip seal shall be made continuous and shall have a minimum thickness of \(^1_4"\). The configuration of the strip seal shall match the configuration of

of 4". The configuration of the strip seal shall match the configuration of the Locking Edge Rails.


The height and thickness of the Locking Edge Rails shown are minimum dimensions. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not be allowed.

The inside of the Locking Edge Rail groove shall be free of weld residue.


Locking Edge Rails may be spliced at slope discontinuities and stage construction laints.

construction joints.

The manufacturer's recommended installation methods shall be followed.



TYPICAL END TREATMENT AT PARAPET



BILL OF MATERIAL (BOTH JOINTS,

Item	Unit	Total
Preformed Joint Strip Seal	Foot	115

PREFORMED JOINT STRIP SEAL STRUCTURE NO. 044-0031

FILE NAME =	USER NAME = cornellim	DESIGNED -	REVISED -		PREFORMED JOINT STRIP SEAL DETAILS	F.A.I. SECTION COUNTY TOTAL SHEETS NO
c:\pw_work\PWIDOT\CORNELLLM\dms47925\0	44-0031-bsmort.dgn	DRAWN ~	REVISED -	STATE OF ILLINOIS	SN 044-0031	24/57 D9 BSMART FY09-1 JOHNSON/PULASKI 20 17
	PLOT SCALE = 1.0000 '/ IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	5N U44-UU31	CONTRACT NO. 78095
L	PLCT DATE = 2/27/2009	DATE -	REVISED -		SCALE: SHEET NO. OF SHEETS STA. TO	O STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT